

SUNEX®
T O O L S

**WAIST HIGH
OR OVER HEAD
COMPONENT SUPPORT**

**1,500 LBS.
UNDER HOIST
STANDS**

**NEW SHORT
STYLE!**

COMING APRIL '23



6811, 6809A and 6810A

1,500 LBS. UNDER HOIST SUPPORT STANDS

- Bearing mounted spin handle and self-locking Acme™ threaded screw provide easy turning and height adjustment under load
- 12" Diameter base for stability and slender design for lightweight, easy handling in close quarters
- Contoured saddle supports most component configurations

6811 - SHORT UNDER HOIST STAND

Designed to support vehicle components only and ideal for applications completed "waist and chest high" on a two-post vehicle lift.

APPLICATIONS:

Shocks/Struts • Brakes/Hubs • Control Arms
Ball Joints • Spindles • Tie Rods • Steering Racks
Aftermarket Part Installation (running boards, bumpers, etc.)



All 3 models include an Acme™ threaded screw with a handle that spins easily for height adjustment



6811



6809A



6810A

6809A & 6810A - UNDER HOIST STANDS

Designed to support vehicle components only and ideal for exhaust system installations and shock absorber replacement.



6810A model includes a foot pedal that provides 1" hands-free lift for micro-adjustments while working



SPECIFICATIONS FOR

	6811	6809A	6810A
Capacity	1,500 Lbs.	1,500 Lbs.	1,500 Lbs.
Minimum Height	35.25"	53"	53"
Maximum Height	57.5"	79"	79"
Base Diameter	12"	12"	12"
Saddle Size	5" x 2.6"	5" x 2.6"	5" x 2.6"
Handle Width	12.9"	12.9"	12.9"
Shipping Weight	27.7 lbs.	29 lbs.	33 lbs.

6811



6809A



6810A

