

**SUNEX**<sup>®</sup>  
T O O L S

**ENGINEERED FOR PERFORMANCE,  
PRECISION, AND ACCESSIBILITY  
IN TIGHT WORKSPACES**



- **Strong 0.5HP Motor** - Delivers high-speed performance for demanding tasks like porting, weld breaking, deburring, and polishing
- **90° Angle Head Design** - Offers improved access in tight or confined spaces, making it ideal for under-dash, engine bay, and frame work
- **Adjustable Power Regulator** - Enables precise speed control for working on different materials with maximum efficiency and safety
- **Lightweight Composite Body** - Weighs just 1.54 lbs. and is built for durability while reducing operator fatigue during long grinding sessions

**SX5208**

## 0.5 HP RIGHT ANGLE DIE GRINDER

90° angle head design improves access in tight or confined spaces, ideal for under-dash, engine bay, and frame work

Ergonomic overmold grip provides a comfortable non-slip hold and reduces vibration for improved handling and control

Adjustable Speed Control

Safety lock trigger helps prevent accidental start-up, adding an extra layer of safety in busy or mobile work environments

Rear exhaust system directs air and debris away from the work surface and operator, maintaining visibility and a cleaner workspace



### SPECIFICATIONS FOR SX5208

Collet Size .....	1/4"
Free Speed .....	18,000 RPM
Length .....	7"
Width .....	3"
Average Air Consumption.....	3.5 CFM

Maximum Air Pressure.....	90 PSI
Air Inlet.....	1/4" NPT
Minimum Hose Size .....	3/8" I.D.
Sound Level .....	82 dBA
Weight .....	1.54 lbs.