

**SUNEX**<sup>®</sup>  
T O O L S

# YOUR GO-TO SOLUTION FOR FAST, POWERFUL SURFACE REMOVAL AND PREP



- **Strong 0.5HP Motor** - Planetary Gear System delivers increased torque and extended tool life, making it ideal for heavy-duty surface preparation and removal tasks
- **180° Rotating Handle** - Allows for superior access and control in tight, awkward, or multi-angle configurations—ideal for hard-to-reach surfaces
- **Adjustable Power Regulator** - Enables precise speed control for working on different materials with maximum efficiency and safety
- **Includes 5 Wheels** - (1) rubber eraser wheel, (3) wire wheels (2 coarse & 1 fine), and (1) stripping wheel to tackle any job
- **Lightweight Composite Body** - Weighs in at only 2.7 lbs. and is built for durability while reducing operator fatigue during long sessions

SX8203

### 0.5 HP SURFACE BLASTER KIT

Protective guard offers safety and compatibility with a wide range of surface prep wheels

180° rotating handle improves accessibility in tight or awkward areas, making it ideal for detailed bodywork or restoration jobs

Ergonomic overmold grip provides a comfortable non-slip hold and reduces vibration for improved handling and control

Adjustable Speed Control

SUNEX

USE APPROVED ACCESSORIES RATED AT HIGHER THAN 4,000 RPM  
DO NOT REMOVE OR OPERATE TOOL WITH OUT REQUIRED GUARD  
INSPECT WHEELS FOR CRACKS OF STRESS BEFORE OPERATING  
KEEP HANDS OFF GUARD AND PROTECTION!  
ALWAYS WEAR EYE BAR & FACE PROTECTION!

WARNING

Safety lock trigger helps prevent accidental start-up, adding an extra layer safety in busy or mobile work environments

Rear exhaust system directs air and debris away from the work surface and operator, maintaining visibility and a cleaner workspace

**Kit Includes:**  
 (1) 4" Rubber Eraser Wheel  
 (3) 4" Wire Wheels (2 coarse & 1 fine)  
 (1) 4" stripping wheel  
 (1) Wheel Hub  
 (1) Hex Allen Key

### SPECIFICATIONS FOR SX8203

Spindle Thread Size .....	9mm
Free Speed .....	4,000 RPM
Length .....	10"
Width .....	5.4"
Average Air Consumption.....	3.5 CFM

Maximum Air Pressure.....	90 PSI
Air Inlet.....	1/4" NPT
Minimum Hose Size .....	3/8" I.D.
Sound Level .....	86 dBA
Weight .....	2.7 lbs. (Tool) / 6.9 lbs. (Kit)